



Plunger Pump Fittings Co., Ltd.



TS2-6206LLUAC3/4C Bearing 2D drawings and 3D CAD models

NTN TS2-6206LLUAC3/4C Single Row Ball Bearings

Bearing No. TS2-6206LLUAC3/4C

Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight	0.198
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C3-Loose Internal Clearance; Steel Cage; C
Other Features	Deep Groove Heat Stabilization Up To 320 Deg F Polyacrylic Rubber Friction Seal



Plunger Pump Fittings Co., Ltd.

Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.439
D	2.441 Inch 62 Millimeter
d	1.181 Inch 30 Millimeter
Outer Race Width	0.63 Inch 16 Millimeter
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	30 mm
precision rating:	ISO Class 0
outside diameter:	62 mm
finish/coating:	Uncoated
overall width:	16 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	16 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	16 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	7300 rpm
internal clearance:	C3
fillet radius:	1 mm
operating temperature range:	-40 to 160 ° C
maximum rpm:	7300 RPM
dynamic load capacity:	19500 N
series:	62



Plunger Pump Fittings Co., Ltd.

static load capacity:	11300 N
manufacturer product page:	Click here