



Plunger Pump Fittings Co., Ltd.



SAK 3/4 Bearing 2D drawings and 3D CAD models

0.75 Inch | 19.05 Millimeter x 0 Inch | 0
 Millimeter x 1.25 Inch | 31.75 Millimeter TIMKEN
 SAK 3/4 Pillow Block Bearings

Bearing No. SAK 3/4

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.66
EAN	0087796156104
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Set Screw
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Relubricatable	Yes
Seals	Contact Shroud
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row Normal Duty Low Base
Long Description	2 Bolt Pillow Block; 3/4" Bore; 1-1/4" Base to Center Height; Set Screw Mount; Ball Bearing; Relubricatable; Cast Iron; Contact Shroud; Non-expansion
Category	Pillow Block



Plunger Pump Fittings Co., Ltd.

UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	SAK 3/4
Weight / LBS	1.463
D	0 Inch 0 Millimeter
Bolt Spacing Minimum	0 Inch 0 Millimeter
Actual Bolt Center to Center	3.8 Inch 96 Millimeter
Nominal Bolt Center to Center	3.8 Inch 97 Millimeter
B	1.25 Inch 31.75 Millimeter
d	0.75 Inch 19.05 Millimeter
Bolt Spacing Maximum	0 Inch 0 Millimeter
Shaft Size d	3/4 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	1.122 in
Dimension T	0.626 in
Dimension D1	1.142 in
Series	Standard
Weight	1.257 lb
Seal Type	Narrow Shroud
Base to Center Height H	31.75 mm
Total Length L	127.00 mm
Total Width A	1.252 in
Bolt Hole Spacing J	96 mm
Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	19.8 mm
Foot Height H1	11.9 mm
Total Height H2	62.7 mm



Plunger Pump Fittings Co., Ltd.

Dimension L1	42.3 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	13.5 mm
Dimension B1	1.252 in
Static Load Rating	1460 lbf
Dynamic Load Rating	3190 lbf